CLAMP TYPE CONNECTORS AND DUPLEX CONNECTORS - DIE-CAST ZINC



Clamp Type Connector



Duplex Connector

APPLICATION

- For use in dry locations to bond flexible metal conduit to a box or enclosure

PRODUCT FEATURE

- Rugged metallic construction ensures mechanical protection for the raceway

COMPLIANCES

- cULus - Standard 514B
  UL FILE E195969
- CSA - C22.2 #18

CATALOG #	TRADE SIZE	UNIT CARTON QTY.	SHIP CARTON QTY.	BAR CODE
Clamp Type Connector – *Die-Cast Zinc*				
2661	3/8"*	100	1000	—
Duplex Connector – *Die-Cast Zinc*				
2611	3/8"*	25	250	—

** For 1/2" knockout*

COMBINATION COUPLINGS - MALLEABLE IRON



Flex - Rigid Couplings

APPLICATIONS

- For use when coupling flexible metal conduit to Rigid/IMC conduit
- Use RACO® Cat. Nos. 1552 - 1554 when coupling threaded Rigid/IMC conduit to flexible metal conduit

PRODUCT FEATURES

- Rugged metallic construction ensures mechanical protection
- Steel/malleable components are zinc-electroplated for added corrosion protection

COMPLIANCE

- UL FILE E195969
- cULus

CATALOG #	TRADE SIZE	UNIT CARTON QTY.	SHIP CARTON QTY.	BAR CODE
Flex to Rigid Couplings – *Malleable Iron*				
1552	1/2"	25	100	—
1553	3/4"	—	25	—
1554	1"	—	25	—



Flex - EMT Squeeze Couplings

FLEX - EMT APPLICATION

- For use when coupling flexible metal conduit to EMT conduit

PRODUCT FEATURES

- Rugged metallic construction ensures mechanical protection
- Steel/malleable components are zinc-electroplated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation

COMPLIANCES

- UL - Standard 514B
- cUL - C22.2 #18

CATALOG #	FLEX SIZE	EMT SIZE	UNIT CARTON QTY.	SHIP CARTON QTY.	BAR CODE
Flex-EMT Squeeze Couplings – *Malleable Iron*					
1941	3/8"	1/2"	—	25	—
1942	1/2"	1/2"	—	25	—
1942-8	1/2"	1/2"	1	25	IIIIIIII
1943	3/4"	3/4"	—	25	—
1943-8	3/4"	3/4"	1	50	IIIIIIII

** Not UL Listed*

SEE END OF SECTION (PG B121) FOR DETAILED DRAWINGS »

90˚ AND DUPLEX CONNECTORS - DIE-CAST ZINC



90˚ Squeeze Type Connector Uninsulated



Duplex Connector

CATALOG #	TRADE SIZE	UNIT CARTON QTY.	SHIP CARTON QTY.	BAR CODE
90˚ Squeeze Type Connector, Uninsulated – *Die-Cast Zinc*				
2691	3/8"*	50	500	—
2692	1/2"	25	250	—
2693	3/4"	10	100	—
Duplex Connector – *Die-Cast Zinc*				
2611	3/8"*	25	250	—

** For 1/2" knockout*

APPLICATIONS

- For use in dry locations to bond armored cable to a box or enclosure

PRODUCT FEATURES

- Rugged metallic construction ensures mechanical protection for the raceway

COMPLIANCES

- UL - Standard 514B
  UL Listed E195969
- CSA - C22.2 #18

SEE END OF SECTION (PG B123) FOR DETAILED DRAWINGS »

CLAMP TYPE AND DUPLEX CONNECTORS - DIE-CAST ZINC



Clamp Type Connector



Duplex Connector

CATALOG #	TRADE SIZE	UNIT CARTON QTY.	SHIP CARTON QTY.	BAR CODE
Clamp Type Cable Connector – *Die-Cast Zinc*				
2661	3/8"*	100	1000	—
Duplex Cable Connector – *Die-Cast Zinc*				
2611	3/8"*	25	250	—

** For 1/2" knockout*

1/2" HUB SIZE FOR MC CABLE - SELECTION CHART	
CLAMP TYPE - *Part No. 2661*	**DIAMETER**
Regular Aluminum Corrugated	.277" - .375"
Aluminum Corrugated	.365" - .510"
Aluminum Smooth	.345" - .525"
Aluminum Interlocked	.455" - .575"
Steel Interlocked	.435" - .547"
DUPLEX - *Part No. 2611*	
Aluminum Smooth	.410" - .500"
Aluminum Interlocked	.460" - .538"
Steel Interlocked	.438" - .560"

APPLICATIONS

- For use in dry locations to connect MC/MCI cable to a box or enclosure

PRODUCT FEATURES

- Rugged metallic construction ensures mechanical protection for the raceway

COMPLIANCES

- UL - Standard 514B
  UL Listed E195969
- CSA - C22.2 #18

SEE END OF SECTION (PG B125) FOR DETAILED DRAWINGS »