



WPSDFCLO



WPSMP



WPSTWES



WPSKRISO



WPSB1



WPSP2



WPSK4



WPSRP1ES



WPSMPCLM PILCLM

WPSYF	WPSYX	WPSDF	WPSDX	WPSRP1	WPSRP2	WPSRR
WPSCP1	WPSCP2	WPSCR	WPSMO	WPSMP	WPSTW	WPSKR
WPSBR	WPSBP1	WPSBP2	WPSB1	WPSB2	WPSB3	WPSTG
WPSPL	WPSP1	WPSP2	WPSP3	WPSP4	WPSP5	WPSP6
WPSK1	WPSK2	WPSK3	WPSK4	WPSK5	WPSK6	WPSK7
WPSK8	WPSK9	WPSK10	WPSK11	WPSMPCLM	WPSMOCLM	CLM
DLM						

WPS

SINGLE GANG WALLBOX DEVICES



WPSMPCLM
Chiller Stop

WPSMPCLM-CHILLER STOP

RED MAINTAINED 40mm MUSHROOM, "PULL TO RESET" (PUSH-PULL)

With Clear Protective Cover Part No. PILCLM



WPSMPCLM
Chiller Stop

WPSMPCLM-EMERGENCY POWER OFF

WPSMPCLM-VENTILATION START

WPSMPCLM-VENTILATION STOP

WPSMPCLM-EMERGENCY STOP

WPSMPCLM-CHILLER STOP

WPSMPCLM-EMERGENCY SHUT-DOWN

WPSMPCLM-EMERGENCY SHUT-OFF

WPSMPCLM-BOILER SHUT-DOWN
WPSMPCLM-HVAC SHUT-DOWN

SERIES WPS EMERGENCY POWER OFF (Standard, Notes 9, 10) Wall Plate Operator Station, 1 Device, Brushed Stainless Steel, Flush Mount only, NEMA 1 (Indoor) Rated. For use with standard 2.13" deep Single gang (2-3/16 x 4") wall box (not supplied). See OPTIONS AVAILABLE further below for other features including alternative standard and Specific Legends. UL LISTED

[Back to List of series and information page](#)

See [Series PIL accessories](#) preceeding page.

WPSMPCLM-Chiller Stop

Actual:

[Blow up](#) | [Normal](#) | [Reduce](#)



[Blow up](#) | [Normal](#) | [Reduce](#)

To print PICTURES, click here: [WPSMPCLM \(Chiller Stop\) -PDF FILE](#)

Drawing:Coming soon

[Blow up](#) | [Normal](#) | [Reduce](#)



[Blow up](#) | [Normal](#) | [Reduce](#)

Description

RED MAINTAINED 40mm MUSHROOM, "PULL TO RESET" (PUSH-PULL) With Clear Protective Cover Part No. PILCLM

OPTIONS AVAILABLE

TO ORDER: The preceding Standard Models in series WPS may be ordered as-is or with optional features listed below. Add desired optional suffix(s) to the indicated Standard Model number chosen from above..

Add suffix SO

Alternative standard legend: EMERGENCY SHUT_OFF (Note 9)

Add suffix ES

Alternative standard legend: EMERGENCY STOP (Note 9)

Add suffix GR

Guarded head for models WPS__ : YF/YX/DF/DX with round push button operators

Add suffix GM

Guard for models WPS__ : MP/TW/KR/MO with 40mm mushroom operators, lockable

ADD suffix IL

Illuminated operator model with 24-120V AC/DC LED (standard). Optional incandescent or neon lamp alos available on some devices (Notes 2, 3, 4, 5)

Add suffix CLO

One Clear Hinged Lockout lid for single device, for WPS__ : YF/YX/DF/DX/PT/P1-P6/K1-K11 (Notes 1, 8)

Add suffix CLM

One Clear Hinged Lockout lid for single device, for WPS__ : MO/MP/TW/KR/K1-K11 (Note 8)

<i>Add suffix DLM</i>	Same as suffix CLM but prevents single mushroom (including momentary) from being released/extended (Note 8)
<i>Add suffix SL</i>	Specific Legend (specify text)
*NOTE:	Contact blocks supplied separately; specify accessories PILNOCB and/or PILNCCB. See Series PIL Accessories pages 4-5. For electrical ratings, see CONTACT BLOCK CHARACTERISTICS at Note 3 page 18.
*NOTE 1:	Short handle only. Compatible with optional suffix CLO and accessory PILCLO single device clear hinged lockout lid.
*NOTE 2 :	Includes 24-120V AC/DC LED (standard). Specify other voltages/extra bright if desired. Optional incandescent or neon lamp available on illuminated (suffix IL) versions of models WPSYF/WPSYX and model WPSPL--add the indicated addendum to suffix IL; IC for incandescent lamp or NE for neon lamp.
*NOTE 3 :	If Illumination is desired, add suffix IL to model number (Notes 2, 4, 5). Not available on models WPS__ : TW/KR/K1-K11.
*NOTE 4:	Model WPSPL devices and illuminated (suffix IL) versions of model WPS__ : YF/YX/DF/DX devices are available in lens colors other than (standard) red. Illuminated (suffix IL) versions of model WPS__ : P1/P2/P3/P4/P5/P6 devices are available in lens colors other than (standard) clear. Add the appropriate addndum to suffix IL as indicated: LR =Red; LC = Clear; LG = Green; LA = Amber; LB =Blue. Keyed selector device models not available with illumination.
*NOTE 5:	Model WPS__ : IL/B1/B2/B3 models require the use of an extra deep wall box.
*NOTE 6:	Unless specified otherwise, "Raise lid - Push botton" stations will be supplied as suffix RP1/CP1 (momentary operator) as standard. For maintained operation of "Raise lid - Push botton" models, specify suffix RP2/CP2.
*NOTE 7:	Models WPSRR/WPSCR "Raise lid - Release button" models require the use of a device {not included} as a pin/lockout/tagout/seal to secure the RR/CR lid in the closed position over the (compressed) type YX extended head round operator. When device is removed, the type YX operator releases/extends, raising the lid. The operator is maintained in the extended position until the lid is reclosed and secured. See PILRRPIN and PILRRLCK at Series PIL Accessories following page.
*NOTE 8:	These items are lockable/sealable. Suffix CLO is compatible with suffix K1-K11 keyed devices without key inserted. Suffix CLM is compatible with suffix K1-K11 devices with and without key inserted. Suffix DLM is for use with MP/TW/KR. For use in accordance with application codes and requirements.
*NOTE 9:	If standard (main) legend EMERGENCY POWER OFF is not desired, add suffix SO or ES as indicated for alternative standard legend or suffix SL for Specific Legend. Also see accessories PILBI/PILCI/PILBL/PILCL for small text on device. (Note 10)
*NOTE 10:	No main legend supplied as standard on these situations. See Note 9 for optional Specific Legend and device text, if desired.
*NOTE: Contact blocks supplied separately; specify normally open PILNOCB and/or normally closed PILNCCB. See Series PIL accessories following page.	

[Back to main page](#)

[Back to List of series and information page](#)